PH-20-STA TECHNICAL DATA SHEET



■ PH-20-STA - 2 LITRE BOILER CONDENSATE PUMP






The 5.5 metre discharge lift helps with the flexibility of the installation. Suitable for both floor and wall mounting and comes with a quick release check valve. Suitable for boilers up to 200kW this version comes with 6 metres of 9.5mm (3/8") ID flexible drain hose.

HANDLES
TEMPS
UP TO 90° C
UP TO 5 MINUTES

■ FEATURES

- 650ml drink cycle at 8.5psi
- Typically 30 seconds run time 3-5 times per day
- Outlet 9.5mm (3/8")
- Suitable for 2.8pH boiler condensate
- 6 metres of 9.5mm (3/8") ID flexible hose
- High-level safety switch
- Suitable for boilers up to 200kW



■ THE PACKAGE

- 2 litre tank pump
- Quick release 1/4 turn check valve
- 6m of 9.5mm (3/8") hose
- 9.5mm to 22mm adaptor
- Hose clip
- Installation instructions





TANK CAP. 1.8L



DECIBEL RATING 43 dB(A)

Part code	Max. lift	Discharge size	Watts	IP	Amps	Volts	Hz
PH-20-STA	5.5m	9.5mm (3/8")	117W	20	1.6A	240V	50Hz

High level alarm	Inlet height	Weight	Cable length	Drink cycle	On level	Off level	Reserve before overflow	Alarm level
Volt free	82.5mm	1.9kg	1.8mm	650ml	30mm	9mm	580ml	50mm

PUMPS
PH-20-STA



Unit 12-14 Sterling Industrial Estate Rainham Road South, Dagenham Essex RM10 8TX www.appheatingdistribution.co.uk